

Breaker TE 500-X



Drilling and Demolition

Applications

- Making or enlarging breaches on masonry walls
- Removing tiles
- Surfacing work on concrete walls
- Corrective chiselling on concrete / masonry walls

Advantages

- More power with less weight
 - Excellent cooling allows various holding positions
 - Low vibration and low contact pressure
 - Separate lubrication chambers
 - Double-sealed hammering mechanism to keep dust out
- Powerful fan keeps parts cool and thus reduces wear

Technical data

Single impact energy	7.5 J
Full hammering frequency	3180 impacts/minute
Max. chiselling performance	900 cm ³ /min
Reduced impact energy	No
A-weighted emission sound pressure level¹⁾	93 dB (A)
Active Vibration Reduction	No
Service indicator	Yes
Triaxial vibration for chiselling in concrete²⁾	15.9 m/s ²
Weight according to EPTA Procedure 01/2003	5 kg

Application

Surface work, Removing plaster/tiles and others, Bushing (roughening, smoothing surface), Corrective chiselling, Penetrations/openings

¹⁾ according to EN 60745
²⁾ according to EN 60745-2-6

HILTI	6 Months	HILTI
Lifetime SERVICE	NO COSTS	FLEET MANAGEMENT
Lifetime REPAIR COST LIMIT	Lifetime MANUFACTURER WARRANTY	



Ordering designation	Package contents	Sales pack quantity	Item number
TE 500-X	1x Breaker TE 500-X 230V GB, 1x Case	1 pc	274736

Please visit our website for the latest item numbers and related products.