



THE ALL-ROUNDER THAT TAKES YOU CLEAN THROUGH.

**Hilti DD 150-U
diamond coring system**



VERSATILE AND POWERFUL.

Hilti DD 150-U diamond coring system

SIMPLY ONE FOR ALL.

Hand-guided or on the drill stand. Wet or dry. The Hilti DD 150-U diamond coring system is clearly the ideal solution for a wide range of drilling applications in concrete or masonry. Equipped with the new Hilti SPX-L core bits or the innovative PCM and HWC core bits, its outstanding performance, efficiency and versatility are simply unique.

APPLICATIONS

- Penetrations for cables and cable trays
- Through-holes for plumbing, heating and ventilation pipes or ducts
- Large-diameter anchors and post-installed rebars
- Installation of hand rails, railings or barriers

ADVANTAGES

- Tremendous versatility: wet and dry coring in various types of materials, all with one system
- Exceptionally user-friendly thanks to self-explanatory design
- The optimum speed for each application
- Less downtime: the service indicator reminds users in good time when servicing is due

HIGHLIGHTS

- Sturdy 3-speed gearing for high coring performance with all diameters up to 162 mm
- High-quality chuck for reliable, easy operation
- Versatile, high-grade drill stand with many useful features
- Clear and concise range of accessories for added versatility



Neat and accurate: hand-guided wet coring in concrete for the installation of pipes or fixtures such as hand rails.



Quick and precise: wet coring in concrete using the drill stand for plumbing and heating pipe installation work.



Virtually dustless dry coring in masonry with the hand-held DD 150-U.



GREAT SERVICES – THE CHOICE IS YOURS.



No matter whether we manage your tools or whether you prefer to own them yourself, they're ready for use at all times – with costs under complete control.

PERFORMANCE DATA

DD 150-U DIAMOND CORING SYSTEM

Rated power (W, 230 V)	2200
Rated speed (r.p.m.) 1st gear / 2nd gear / 3rd gear	780 / 1520 / 2850
Coring diameter range (mm)	12 – 162 (optimum 12 - 152)
Suitable core bits	SPX-L, HDM, PCM, HWC
Max. coring depth (mm)	450
Dimensions, motor unit / system, LxWxH (mm)	516x129x159 / 610x250x952
Weight as per EPTA 01/2003, motor unit / system (kg)	8.2 / 21.5

Right of technical changes reserved.

DD 150-U DIAMOND CORING SYSTEM

ACCESSORIES

Order designation		Item number
DD 150-U diamond coring system with BI+ chuck		433331
Order designation		Item number
DD-ST 150-U CTL drill stand with vacuum base plate and tilt mechanism	①	435666
DD-HW-3A hand wheel	②	2007687
DD-HW-2A hand wheel	③	2007688
DD M12 L set for CTL drill stand		409279
DD-ST-150/160-JS jack screw	④	2007686
DD-ST-150/160-RR rota-rail	⑤	2006373
DD-WCS-HH-150 water collector holder (for hand-guided use)		2008130
DD-ST-150/160-WCH water collector holder (for drill stand use)		2016633
DD-WC-S water collector		232204
DD-WC-SM water collector		232221
DWP 10 water supply unit (10 l)		365595
DD-WMS 100 water management system	⑥	2145821
VC 40-UL wet / dry vacuum cleaner		2114605

