

CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV

Safety Data Sheet

according to the Model Work Health and Safety Regulations
Issue date: 30/11/2021

Revision date:

Version: 1.0

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form	Mixture
Trade name	CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV
Product code	BU Fire Protection Foam

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

No additional information available

1.4. Details of manufacturer or importer

Supplier

Hilti (Aust.) Pty. Ltd.
Level 5, 1G Homebush Bay Drive
P.O. Box 3217
2138 Rhodes NSW - Australia
T +61 131 292 - F +61 1300 135 042
serviceaustralia@hilti.com

Department issuing data specification sheet:

Hilti AG
Feldkircherstraße 100
9494 Schaan - Liechtenstein
T +423 234 2111
chemicals.hse@hilti.com

1.5. Emergency phone number

Emergency number	+61 2 8748 1000
------------------	-----------------

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Respiratory sensitisation, Category 1	H334
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Reproductive toxicity, Additional category, Effects on or via lactation	H362
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373
Hazardous to the aquatic environment — Chronic Hazard, Category 4	H413

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU)



Signal word (GHS AU)

Danger

Hazard statements (GHS AU)

H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction

CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Precautionary statements (GHS AU)	<p>H319 - Causes serious eye irritation H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled H335 - May cause respiratory irritation H351 - Suspected of causing cancer H362 - May cause harm to breast-fed children H373 - May cause damage to organs through prolonged or repeated exposure H413 - May cause long lasting harmful effects to aquatic life</p> <p>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe spray. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.</p>
-----------------------------------	---

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
4,4'-diphenylmethanediisocyanate, isomeres and homologues	9016-87-9	10 – 30	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
tris(2-chloro-1-methylethyl) phosphate	13674-84-5	5 – 10	Acute Tox. 4 (Oral), H302
Alkanes, C14-17, chloro (MCCP, Medium chained chlorinated paraffins)	85535-85-9	5 – 10	Lact., H362 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Get immediate medical advice/attention.
First-aid measures after skin contact	Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	Call a poison center or a doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting.

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation	May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Symptoms/effects after skin contact	Irritation. May cause an allergic skin reaction. Causes skin irritation.
Symptoms/effects after eye contact	Eye irritation. Causes serious eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	Extremely flammable aerosol.
Explosion hazard	Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	Toxic fumes may be released. Vapours may form explosive mixture with air.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe spray. Avoid contact with skin and eyes. Evacuate unnecessary personnel.
----------------------	---

6.1.2. For emergency responders

Protective equipment	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up	Mechanically recover the product. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact during pregnancy/while nursing. Do not breathe spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. May form flammable/explosive vapour-air mixture. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing spray.
Hygiene measures	Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV

Safety Data Sheet

according to the Model Work Health and Safety Regulations

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep cool. Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 – 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight. Keep away from ignition sources.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

No additional information available

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment Gloves. Protective clothing. Safety glasses. Avoid all unnecessary exposure.

Hand protection Protective gloves. Wear protective gloves.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	3 (> 60 minutes)			EN ISO 374

Eye protection Chemical goggles or safety glasses

Type	Field of application	Characteristics	Standard
Safety glasses			EN 166, EN 171

Skin and body protection Wear suitable protective clothing

Respiratory protection Not necessary with sufficient ventilation. In case of inadequate ventilation wear respiratory protection.

Device	Filter type	Condition	Standard
Aerosol mask	Type A - High-boiling (>65 °C) organic compounds		

Personal protective equipment symbol(s)



Environmental exposure controls Avoid release to the environment.

Consumer exposure controls Avoid contact during pregnancy/while nursing.

Other information Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Physical state Liquid

CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Appearance	Aerosol.
Colour	light brown
Odour	slight ether-like odour
Odour threshold	No data available
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	-42 °C
Flash point	-104 °C
Auto-ignition temperature	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Relative density	No data available
Density	Density : 1 g/cm ³
Solubility	No data available
Partition coefficient n-octanol/water (Log Pow)	No data available
Explosive properties	No data available
Explosive limits	No data available
Minimum ignition energy	No data available
Fat solubility	No data available

SECTION 10: Stability and reactivity

Reactivity	Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	Stable under normal conditions. Not established.
Possibility of hazardous reactions	Heating may cause a fire or explosion. Not established.
Conditions to avoid	Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	No additional information available. fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
LD50 oral rat	> 10000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature study, Dermal)
Alkanes, C14-17, chloro (MCCP, Medium chained chlorinated paraffins) (85535-85-9)	
LD50 oral rat	> 4000 mg/kg bodyweight (Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 13500 mg/kg bodyweight (24 h, Rabbit, Read-across, Dermal)
LC50 Inhalation - Rat	> 48.17 mg/l air (1 h, Rat, Read-across, Inhalation (vapours))
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	
LD50 oral rat	1101 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 oral	1150 – 1750
LD50 dermal rabbit	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))

CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV

Safety Data Sheet

according to the Model Work Health and Safety Regulations

tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	
LC50 Inhalation - Rat	> 5 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Suspected of causing cancer.
Reproductive toxicity	May cause harm to breast-fed children.
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not classified
CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV	
Vaporizer	Aerosol

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified.
Hazardous to the aquatic environment, long-term (chronic)	May cause long lasting harmful effects to aquatic life.

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
LC50 - Other aquatic organisms [1]	> 1000 mg/l (96 h, Literature study)
BCF - Fish [1]	1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	10.46 (Calculated, KOWWIN)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9.078 – 10.597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Alkanes, C14-17, chloro (MCCP, Medium chained chlorinated paraffins) (85535-85-9)	
LC50 - Fish [1]	> 5000 mg/l (Equivalent or similar to OECD 203, 96 h, Alburnus alburnus, Static system, Brackish water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	0.006 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	> 3.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF - Fish [1]	6660 – 9140 l/kg (OECD 305: Bioconcentration: Flow-Through Fish Test, 35 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	4.7 – 8.3 (Experimental value, Equivalent or similar to OECD 117)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	5 – 5.2 (log Koc, Experimental value)
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	
LC50 - Fish [1]	51 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	131 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	82 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
BCF - Fish [1]	0.8 – 2.8 (OECD 305: Bioconcentration: Flow-Through Fish Test, 6 week(s), Pisces, Flow-through system, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	2.68 (Experimental value, Equivalent or similar to OECD 117)

CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV

Safety Data Sheet

according to the Model Work Health and Safety Regulations

tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.24 (log Koc, OECD 106: Adsorption/Desorption Using a Batch Equilibrium Method, Read-across)

12.2. Persistence and degradability

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.
Alkanes, C14-17, chloro (MCCP, Medium chained chlorinated paraffins) (85535-85-9)	
Persistence and degradability	Not readily biodegradable in the soil. Not readily biodegradable in water.
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
BCF - Fish [1]	1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	10.46 (Calculated, KOWWIN)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9.078 – 10.597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Alkanes, C14-17, chloro (MCCP, Medium chained chlorinated paraffins) (85535-85-9)	
BCF - Fish [1]	6660 – 9140 l/kg (OECD 305: Bioconcentration: Flow-Through Fish Test, 35 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	4.7 – 8.3 (Experimental value, Equivalent or similar to OECD 117)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	5 – 5.2 (log Koc, Experimental value)
Bioaccumulative potential	High potential for bioaccumulation (BCF > 5000).
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	
BCF - Fish [1]	0.8 – 2.8 (OECD 305: Bioconcentration: Flow-Through Fish Test, 6 week(s), Pisces, Flow-through system, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	2.68 (Experimental value, Equivalent or similar to OECD 117)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.24 (log Koc, OECD 106: Adsorption/Desorption Using a Batch Equilibrium Method, Read-across)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
Partition coefficient n-octanol/water (Log Pow)	10.46 (Calculated, KOWWIN)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology 9.078 – 10.597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Adsorbs into the soil.
Alkanes, C14-17, chloro (MCCP, Medium chained chlorinated paraffins) (85535-85-9)	
Partition coefficient n-octanol/water (Log Pow)	4.7 – 8.3 (Experimental value, Equivalent or similar to OECD 117)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology 5 – 5.2 (log Koc, Experimental value)
Ecology - soil	Low potential for mobility in soil.
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Pow)	2.68 (Experimental value, Equivalent or similar to OECD 117)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology 2.24 (log Koc, OECD 106: Adsorption/Desorption Using a Batch Equilibrium Method, Read-across)
Ecology - soil	Low potential for adsorption in soil.

CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV

Safety Data Sheet

according to the Model Work Health and Safety Regulations

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV	
Fluorinated greenhouse gases	False
4,4'-diphenylmethanediisocyanate, isomers and homologues (9016-87-9)	
Fluorinated greenhouse gases	False
Alkanes, C14-17, chloro (MCCP, Medium chained chlorinated paraffins) (85535-85-9)	
Fluorinated greenhouse gases	False
tris(2-chloro-1-methylethyl) phosphate (13674-84-5)	
Fluorinated greenhouse gases	False

SECTION 13: Disposal considerations

Waste treatment methods	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV

Safety Data Sheet

according to the Model Work Health and Safety Regulations

14.6. Special precautions for user

Overland transport

Classification code (ADR)	5F
Special provisions (ADR)	190, 327, 344, 625
Limited quantities (ADR)	1I
Packing instructions (ADR)	P207, LP02
Mixed packing provisions (ADR)	MP9
Transport category (ADR)	2
Tunnel restriction code (ADR)	D

Transport by sea

Special provisions (IMDG)	63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	SP277
Packing instructions (IMDG)	P207, LP02
EmS-No. (Fire)	F-D
EmS-No. (Spillage)	S-U
Stowage category (IMDG)	None
MFAG-No	126

Air transport

PCA packing instructions (IATA)	203
PCA max net quantity (IATA)	75kg
CAO packing instructions (IATA)	203
Special provisions (IATA)	A145, A167, A802

Inland waterway transport

Classification code (ADN)	5F
Special provisions (ADN)	19, 327, 344, 625
Limited quantities (ADN)	1 L
Excepted quantities (ADN)	E0
Equipment required (ADN)	PP, EX, A
Ventilation (ADN)	VE01, VE04
Number of blue cones/lights (ADN)	1

Rail transport

Special provisions (RID)	190, 327, 344, 625
Limited quantities (RID)	1L
Packing instructions (RID)	P207, LP02

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

14.8. Hazchem or Emergency Action Code

Hazchem Code Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status All the chemicals contained in this product are listed introductions

15.2. International agreements

No additional information available

CF-I 50 ECO GV/ CF-F 750/ CF-F 750-GV

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 16: Other information

Classification:

Aerosol 1	H222;H229
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 2	H351
Lact.	H362
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 4	H413

Full text of H-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Lact.	Reproductive toxicity, Additional category, Effects on or via lactation
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H362	May cause harm to breast-fed children
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

SDS_AU_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.