

HIT-RE 500 V3

en	This safety data sheet file is issued for the following production lots: 1. Version 2.3 is valid for HIT-RE 500 V3 with a maximum expiration date of 12/2024 (see foil pack manifold) 2. Version 3.0 is valid for HIT-RE 500 V3 with a minimum expiration date of 01/2025 (see the foil pack manifold)
de	Diese Sicherheitsdatenblatt-Datei betrifft die folgenden Fertigungslose: 1. Version 2.3 ist gültig für HIT-RE 500 V3 mit einem Haltbarkeitsdatum bis 12/2024 (siehe Verbindungsteil) 2. Version 3.0 ist gültig für HIT-RE 500 V3 mit einem Haltbarkeitsdatum ab 01/2025 (siehe Verbindungsteil)
nl	Dit veiligheidsinformatiebladbestand wordt afgegeven voor de volgende productie-lots: 1. Versie 2.3 is geldig voor HIT-RE 500 V3 met een maximale houdbaarheidsdatum tot 12/2024 (zie foliepak verdeler) 2. Versie 3.0 is geldig voor HIT-RE 500 V3 met een minimale houdbaarheidsdatum tot 01/2025 (zie foliepak verdeler)
fr	Ce fichier de données de sécurité est délivré pour les lots de production suivants : 1. La version 2.3 est valide pour HIT-RE 500 V3 avec une date d'expiration maximale de 12/2024 (voir le raccord de cartouche souple) 2. La version 3.0 est valide pour HIT-RE 500 V3 avec une date d'expiration maximale de 01/2025 (voir le raccord de cartouche souple)
da	Denne sikkerhedsdatabladfil er udgivet for følgende produktions lots: 1. Version 2.3 er gældende for HIT-RE 500 V3 med en maksimal udløbsdato d. 12/2024 (se foliepakkens manifold) 2. Version 3.0 er gældende for HIT-RE 500 V3 med en mindste udløbsdato d. 01/2025 (se foliepakkens manifold)
sv	Denna säkerhetsdatabladfil har utfärdats för följande tillverkningspartier: 1. Version 2.3 är giltig för HIT-RE 500 V3 med ett sista giltighetsdatum den 12/2024 (se folieförpackningens grenrör) 2. Version 3.0 är giltig för HIT-RE 500 V3 med ett första giltighetsdatum den 01/2025 (se folieförpackningens grenrör)
fi	Tämä käyttöturvallisuustiedote koskee seuraavia tuotantoeriä: 1. Versio 2.3 koskee HIT-RE 500 V3 -tuotetta, jonka viimeinen käyttöpäivämäärä on 12/2024 tai sitä ennen (ks. foliopakkauksen taite) 2. Versio 3.0 koskee HIT-RE 500 V3 -tuotetta, jonka viimeinen käyttöpäivämäärä on 01/2025 tai sen jälkeen (ks. foliopakkauksen taite)
hu	Ezt a biztonsági adatlapot a következő gyártási tétélekhez bocsátják ki: 1. Az 2.3 változat legfeljebb 2024/12 lejáratú dátummal érvényes a HIT-RE 500 V3-re (lásd a fóliacsomag sokszorosított iratát) 2. Az 3.0 változat legalább 2025/01 lejáratú dátummal érvényes a HIT-RE 500 V3-re (lásd a fóliacsomag sokszorosított iratát)
es	Este archivo de hoja de datos de seguridad se emite para los siguientes lotes de producción: 1. Versión 2.3 válida para HIT-RE 500 V3 con una fecha de caducidad máxima de 12/2024 (consulte el colector de láminas) 2. Versión 3.0 válida para HIT-RE 500 V3 con una fecha de caducidad mínima de 01/2025 (consulte el colector de láminas)
pt	Este ficheiro com ficha de dados de segurança é emitido para os seguintes lotes de produção: 1. A versão 2.3 é válida para a HIT-RE 500 V3 com um prazo máximo de validade até 12/2024 (ver as diversas embalagens) 2. A versão 3.0 é válida para a HIT-RE 500 V3 com um prazo mínimo de validade até 01/2025 (ver as diversas embalagens)
it	Questo file della scheda tecnica di sicurezza è rilasciato per i seguenti lotti di produzione: 1. La versione 2.3 è valida per HIT-RE 500 V3 con data di scadenza massima 12/2024 (vedere la giunzione della confezione) 2. La versione 3.0 è valida per HIT-RE 500 V3 con data di scadenza minima 01/2025 (vedere la giunzione della confezione)
pl	Ten plik arkusza danych bezpieczeństwa jest wydany dla następujących części produkcyjnych: 1. Wersja 2.3 obowiązuje w przypadku HIT-RE 500 V3 z maksymalnym dniem rozpoczęcia pracy 12/2024 (patrz opakowanie foliowe) 2. Wersja 3.0 obowiązuje w przypadku HIT-RE 500 V3 z minimalnym dniem rozpoczęcia pracy 01/2025 (patrz opakowanie foliowe)
ru	Этот файл сертификата безопасности предоставлен для следующих партий продукции: 1. Версия 2.3 действительна для HIT-RE 500 V3 с максимальным сроком годности до 12.2024 г. (см. присоединительную часть на капсуле) 2. Версия 3.0 действительна HIT-RE 500 V3 с минимальным сроком годности до 01.2025 г. (см. присоединительную часть на капсуле)
el	Το παρόν δελτίο δεδομένων ασφαλείας εκδίδεται για τις ακόλουθες παρτίδες παραγωγής: 1. Η έκδοση 2.3 ισχύει για το HIT-RE 500 V3 με μέγιστη ημερομηνία λήξης τον 12/2024 (βλέπε διανομέα συσκευασίας μεμβράνης) 2. Η έκδοση 3.0 ισχύει για το HIT-RE 500 V3 με ελάχιστη ημερομηνία λήξης τον 01/2025 (βλέπε τον διανομέα της συσκευασίας μεμβράνης)
cs	Tento soubor s bezpečnostním listem je vystaven pro tyto výrobní závody 1. Verze 2.3 je platná pro HIT-RE 500 V3 s maximálním datem expirace 12/2024 (viz fólie balení) 2. Verze 3.0 je platná pro HIT-RE 500 V3 s minimálním datem expirace 01/2025 (viz fólie balení)
bg	Този информационен лист за безопасност се публикува за следните производствени партии: 1. Версия 2.3 е валидна за HIT-RE 500 V3 с максимален срок на валидност до 12.2024 г. (вж. фолийна опаковка за колектор) 2. Версия 3.0 е валидна за HIT-RE 500 V3 с минимален срок на изтичане 01.2025 г. (вж. фолийна опаковка за колектор)
lv	Šo drošības datu lapa ir izsniegta šādām ražojumu partijām: 1. Versija 2.3 ir derīga izstrādājumiem HIT-RE 500 V3, kura maksimālais derīguma termiņš ir 2024. gada maijs (skatīt folija iepakojuma kolektoru) 2. Versija 3.0 ir derīga izstrādājumiem HIT-RE 500 V3, kura minimālais derīguma termiņš ir 2025. gada jūnijs (skatīt folija iepakojuma kolektoru)
lt	Šis saugos duomenų lapo failas išduodamas šioms gamybos partijoms: 1. 2.3 versija galioja HIT-RE 500 V3, kurios maksimali galiojimo data – 2024-12 (žr. folinių pakuočių rinkinį) 2. 3.0 versija galioja HIT-RE 500 V3, kurios minimali galiojimo data – 2025-01 (žr. folinių pakuočių rinkinį)
sk	Tento súbor bezpečnostných údajov sa vydáva pre tieto výrobné šarže: 1. Verzia 2.3 je platná pre HIT-RE 500 V3 s maximálnym dátumom expirácie 12/2024 (pozrite si údaj na fólii balenia) 2. Verzia 3.0 je platná pre HIT-RE 500 V3 s minimálnym dátumom expirácie 01/2025 (pozrite si údaj na fólii balenia)
sl	Datoteka z varnostnim listom je izdana za naslednje proizvodne serije: 1. Različica 2.3 je veljavna za izdelek HIT-RE 500 V3 z maksimalnim datumom poteka veljavnosti: 12/2024 (glejte pakiranje) 2. Različica 3.0 je veljavna za izdelek HIT-RE 500 V3 z minimalnim datumom poteka veljavnosti: 01/2025 (glejte pakiranje)

HIT-RE 500 V3

et	See ohutuskaardi fail on välja antud järgmistele tootepartiidele: 1. Versioon 2.3 kehtib tootele HIT-RE 500 V3 viimase säilimiskuupäevaga 12/2024 (vt fooliumpakendi hargnemiskohta) 2. Versioon 3.0 kehtib tootele HIT-RE 500 V3 esimese säilimiskuupäevaga 01/2025 (vt fooliumpakendi hargnemiskohta)
ro	Acest fișier cu date tehnice de securitate este emis pentru următoarele locuri de producție: 1. Versiunea 2.3 este valabilă pentru HIT-RE 500 V3 cu data maximă de expirare 12/2024 (a se vedea racordul pentru cartușe din folie) 2. Versiunea 3.0 este valabilă pentru HIT-RE 500 V3 cu data minimă de expirare 01/2025 (a se vedea racordul pentru cartușe din folie)
hr	Ovaj sigurnosno-tehnički list izdaje se za sljedeće proizvodne serije: 1. Verzija 2.3 vrijedi za HIT-RE 500 V3 s maksimalnim rokom trajanja do 12/2024 (vidjeti razvodnik iz folije) 2. Verzija 3.0 vrijedi za HIT-RE 500 V3 s minimalnim rokom trajanja do 01/2025 (vidjeti razvodnik iz folije)
tr	Bu güvenlik bilgi formu dosyası aşağıdaki üretim partileri için hazırlanmıştır: 1. Versiyon 2.3, maksimum son kullanma tarihi 12/2024 olan HIT-RE 500 V3 için geçerlidir (bkz. folyo paketi manifoldu) 2. Versiyon 3.0, inimumm son kullanma tarihi 01/2025 olan HIT-RE 500 V3 için geçerlidir (bkz. folyo paketi manifoldu)
uk	Цей файл сертифіката безпеки надано для наступних партій продукції: 1. Версія 2.3 дійсна для HIT-RE 500 V3 з максимальним терміном придатності до 12.2024 р. (див. приєднувальну частину на капсулі) 2. Версія 3.0 дійсна для HIT-RE 500 V3 з мінімальним терміном придатності до 01.2025 р. (див. приєднувальну частину на капсулі)
zh	本安全数据表文件针对以下生产批次发布： 1. 版本 2.3 对 HIT-RE 500 V3 有效，最长失效日期为 2024 年 12 月（参见箔包装歧管） 2. 版本 3.0 对 HIT-RE 500 V3 有效，最短失效日期为 2025 年 1 月（参见箔包装歧管）
ar	يتم إصدار ملف صحيفة بيانات السلامة لتشغيلات الإنتاج التالية: 1. الإصدار 2.3 صالح لـ HIT-RE 500 V3 بعد أقصى لتاريخ انتهاء الصلاحية هو 2024/12 (انظر العبوة المصنوعة من رقائق الألومنيوم) 2. الإصدار 3.0 صالح لـ HIT-RE 500 V3 على الأقل لتاريخ انتهاء الصلاحية هو 2025/1 (انظر العبوة المصنوعة من رقائق الألومنيوم)
ja	この安全性データシートファイルは、次の生産ロット用に発行されています： 1. バージョン 2.3 は、有効期限が最大 2024 年 12 月までの HIT-RE 500 V3 に対して有効です (フォイルパック連結部に表示) 2. バージョン 3.0 は、有効期限が 2025 年 1 月以降の HIT-RE 500 V3 に対して有効です (フォイルパック連結部に表示)
sr	Datoteka bezbednosnog lista se izdaje za sledeće proizvodne serije: 1. Verzija 2.3 je dostupna za HIT-RE 500 V3 sa maksimalnim datumom isteka 12/2024 (pogledajte ivicu pakovanja od folije) 2. Verzija 3.0 je dostupna za HIT-RE 500 V3 sa minimalnim datumom isteka 01/2025 (pogledajte ivicu pakovanja od folije)
ms	Fail helaian data keselamatan ini dikeluarkan untuk lot pengeluaran yang berikut: 1. Versi 2.3 adalah sah untuk HIT-RE 500 V3 dengan tarikh tamat tempoh maksimum pada 12/2024 (lihat manifold pek kerajang) 2. Versi 3.0 adalah sah untuk HIT-RE 500 V3 dengan tarikh tamat tempoh minimum pada 01/2025 (lihat manifold pek kerajang)
ko	본 안전보건자료는 다음 제품 로트에 대해 발급되었습니다. 1. 버전 2.3(은)는 HIT-RE 500 V3에 대해 유효하며, 최대 만료 기한은 2024년 12월입니다(호일 팩 매니폴드 참조) 2. 버전 3.0(은)는 HIT-RE 500 V3에 대해 유효하며, 최소 만료 기한은 2025년 1월입니다(호일 팩 매니폴드 참조)
id	File lembar data keselamatan ini diterbitkan untuk lot produksi berikut: 1. Versi 2.3 berlaku untuk HIT-RE 500 V3 dengan tanggal kedaluwarsa maksimum 12/2024 (lihat foil pack manifold) 2. Versi 3.0 berlaku untuk HIT-RE 500 V3 dengan tanggal kedaluwarsa minimum 01/2025 (lihat foil pack manifold)
he	קובץ גיליון נתוני בטחונות זה מופק עבור מגרשי הייצור הבאים: 1. גרסה 2.3 תקפה ל-HIT-RE 500 V3 עם תאריך תפוגה מקסימלי של 12/2024 (ראה יריעת foil pack) 2. גרסה 3.0 תקפה ל-HIT-RE 500 V3 עם תאריך תפוגה מינימלי של 01/2025 (ראה יריעת foil pack)
th	แผนข้อมูลด้านความปลอดภัยนี้จัดทำสำหรับล็อตการผลิตดังต่อไปนี้: 1. เวอร์ชัน 2.3 ใช้ได้กับ HIT-RE 500 V3 ที่มีวันหมดอายุไม่เกิน 12/2024 (โปรดดูแผนพับห่อฟอยล์) 2. เวอร์ชัน 3.0 ใช้ได้กับ HIT-RE 500 V3 ที่มีวันหมดอายุขั้นต่ำ 01/2025 (โปรดดูแผนพับห่อฟอยล์)
vi	Tệp bảng dữ liệu an toàn này được phát hành cho các lô sản xuất sau: 1. Phiên bản 2.3 hợp lệ cho HIT-RE 500 V3 với ngày hết hạn tối đa là 12/2024 (xem ống keo cấy thép) 2. Phiên bản 3.0 hợp lệ cho HIT-RE 500 V3 với ngày hết hạn tối thiểu là 01/2025 (xem ống keo cấy thép)
zh tw	下列生產批次將獲核發本安全資料表檔案： 1. 2.3 版適用於 HIT-RE 500 V3，最長到期日 12/2024 (請見鋁箔包打字紙) 2. 3.0 版適用於 HIT-RE 500 V3，最短到期日 01/2025 (請見鋁箔包打字紙)
kk	Бұл қауіпсіздік паспорты мына өндірістік партиялар үшін шығарылады: 1. 2.3 нұсқасы жарамдылық мерзімі көп уақытты (12/2024) қамтитын HIT-RE 500 V3 үшін жарамды (жұқалтыр қаптаманы қараңыз) 2. 3.0 нұсқасы жарамдылық мерзімі аз уақытты (01/2025) қамтитын HIT-RE 500 V3 үшін жарамды (жұқалтыр қаптаманы қараңыз)

HIT-RE 500 V3

Safety information for 2-Component-products

Issue date: 08/12/2022

Revision date: 08/12/2022

Supersedes: 13/05/2020

Version: 3.0

SECTION 1: Kit identification

1.1 Product identifier

Product name

HIT-RE 500 V3



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti Far East Private Ltd.
80 Pasir Panjang Road,
#16-83/84 Mapletree Business City
117372 Singapore - Singapur
T +65 6777 7887 - F +65 6777 3057
sg-customerservice@hilti.com

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

GHS SG classification

Health hazards

Skin corrosion/irritation, Category 1B
Serious eye damage/eye irritation, Category 1
Skin sensitisation, Category 1
Specific target organ toxicity – Single exposure, Category 3
Hazardous to the aquatic environment – Chronic Hazard, Category 2

Environmental hazards

Label elements

GHS SG labelling

Hazard pictograms (GHS SG)



GHS05



GHS07



GHS09

Signal word (GHS SG)

Danger

Hazardous ingredients

Epoxy resin, Amines

Hazard statements (GHS SG)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.

HIT-RE 500 V3


Safety information for 2-Component-products

Precautionary statements (GHS SG)

H335 - May cause respiratory irritation.
H411 - Toxic to aquatic life with long lasting effects.
P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

Additional information

2-component-foilpack, contains:
Component A: Epoxy resin, Reactive diluent, inorganic filler
Component B: Amine hardener, inorganic filler



Name	General description	Quantity	Unit	GHS SG classification
HIT-RE 500 V3, B		1	pcs (pieces)	Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335
HIT-RE 500 V3, A		1	pcs (pieces)	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411

SECTION 4: General advice

General advice For professional users only

SECTION 5: Safe handling advice

General measures	Spilled material may present a slipping hazard
Environmental precautions	Prevent entry to sewers and public waters Notify authorities if liquid enters sewers or public waters Avoid release to the environment Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.
Storage conditions	Protect from sunlight. Store in a well-ventilated place.
Technical measures	Comply with applicable regulations
Precautions for safe handling	Wear personal protective equipment Avoid contact with skin and eyes Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work Avoid contact during pregnancy/while nursing
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation Mechanically recover the product On land, sweep or shovel into suitable containers Store away from other materials.
For containment	Collect spillage.
Incompatible materials	Sources of ignition Direct sunlight
Incompatible products	Strong bases Strong acids

HIT-RE 500 V3

Safety information for 2-Component-products

SECTION 6: First aid measures

First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist
First-aid measures after ingestion	Do not induce vomiting Rinse mouth Immediately call a POISON CENTER/doctor.
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures general	Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after eye contact	Causes serious eye damage.
Symptoms/effects after skin contact	May cause an allergic skin reaction.
Other medical advice or treatment	Treat symptomatically

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014
Issue date: 08.12.2022

Revision date: 08.12.2022

Supersedes: 13.05.2020

Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Name HIT-RE 500 V3, A
Product code BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended uses and restrictions For professional use only
Recommended use Composite mortar component for fasteners in the construction industry

1.4. Supplier's details

Supplier

Hilti Far East Private Ltd.
80 Pasir Panjang Road, #16-83/84 Mapletree Business City Singapore
Singapur 117372
T +65 6777 7887 - F +65 6777 3057
sg-customerservice@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6 Kaufering Deutschland 86916
T +49 8191 906876
anchor.hse@hilti.com

1.5. Emergency phone number

Emergency number Schweizerisches Toxikologisches Informationszentrum – 24h Service
+41 44 251 51 51 (international)
+65 6777 7887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Health hazards Skin corrosion/irritation, Category 2
Serious eye damage/eye irritation, Category 1
Skin sensitisation, Category 1
Environmental hazards Hazardous to the aquatic environment – Chronic Hazard, Category 2

2.2. GHS label elements including precautionary statements

Hazard pictograms (GHS SG)



Signal word (GHS SG)

Danger

Hazard statements (GHS SG)

H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H411 : Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P280 : Wear eye protection, protective clothing, protective gloves.
P262 : Do not get in eyes, on skin, or on clothing.

Response

P305+P351+P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 : If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 : If eye irritation persists: Get medical advice/attention.
P302+P352 : IF ON SKIN: Wash with plenty of soap and water.

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Synonyms	Concentration (%)	Formula	Product identifier
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane / 2,2-bis(4-(2,3-epoxypropyloxy)phenyl)propane / 2,2-bis(4-glycidyoxyphenyl)propane	25 – 40	C ₂₁ H ₂₄ O ₄	CAS-No.: 1675-54-3 EC-No.: 216-823-5
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	-	10 – 20	(C ₆ H ₆ O.C ₃ H ₅ ClO.CH ₂ O) _x	CAS-No.: 9003-36-5 EC-No.: 500-006-8
Trimethylol ethane triglycidyl ether Polymer	-	5 – 10	-	CAS-No.: 68460-21-9
butanedioldiglycidyl ether	1,4-bis(2,3-epoxypropoxy)butane / 1,4-bis(2,3-epoxypropyloxy)butane / 1,4-bis(glycidyoxy)butane	5 – 10	C ₁₀ H ₁₈ O ₄	CAS-No.: 2425-79-8 EC-No.: 219-371-7 EC Index-No.: 603-072-00-7
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	((3-(trimethoxysilyl)propoxy)methyl)oxirane / [3-(2,3-epoxypropoxy)propyl]trimethoxysilane / 1-(glycidyoxy)-3-(trimethoxysilyl)propane	2.5 – 5	C ₉ H ₂₀ O ₅ Si	CAS-No.: 2530-83-8 EC-No.: 219-784-2

SECTION 4: First-aid measures

4.1. Description of necessary first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
Inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
Skin contact	Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get immediate medical advice/attention.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
Ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after skin contact	Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye irritation.

4.3. Indication of immediate medical attention and special treatment needed

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Special protective actions for fire fighters

Firefighting instructions Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

6.3. Methods and material for containment and cleaning up

For containment Collect spillage.
Methods for cleaning up This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene measures Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions Protect from sunlight.
Incompatible products Strong bases. Strong acids.
Incompatible materials Sources of ignition. Direct sunlight.
Storage temperature 5 – 25 °C
Heat and ignition sources Keep away from heat and direct sunlight.

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters/Occupational exposure limits

No additional information available

8.2. Monitoring

No additional information available

8.3. Appropriate engineering control measures

Appropriate engineering controls

Ensure adequate ventilation.

8.4. Personal protection

Materials for protective clothing

Long sleeved protective clothing

Hand protection

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN ISO 374

Eye protection

Wear security glasses which protect from splashes

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Personal protective equipment symbol(s)



Environmental exposure controls

No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.

Consumer exposure controls

Avoid contact during pregnancy/while nursing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Light grey
Odour	characteristic
Odour threshold	No data available
pH	6.6
Relative evaporation rate (butylacetate=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

Density	1.45 g/cm ³
Solubility	insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	No data available
Partition coefficient n-octanol/water (Log Kow)	No data available
Viscosity, dynamic	45 – 59 Pa·s 23 °C
Explosive properties	No data available
Oxidising properties	No data available
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Acute toxicity

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Experimental value)
LD50 oral	11400 mg/kg
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
LD50 oral rat	> 5000 mg/kg bodyweight (Rat; ECHA)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; ECHA)
butanedioldiglycidyl ether (2425-79-8)	
LD50 oral rat	2980 mg/kg (Rat)
LD50 oral	1163 mg/kg (Rat; Exp. Key study ECHA)
LD50 dermal rabbit	1130 mg/kg (Rabbit)

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LD50 oral rat	8025 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	4250 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
Skin corrosion/irritation	Causes skin irritation. pH: 6.6
Serious eye damage/irritation	Causes serious eye damage.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-RE 500 V3, A	
Density	1.45 g/cm ³
Potential adverse human health effects and symptoms	No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Toxic to aquatic life with long lasting effects.
Other information	Avoid release to the environment.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LC50 - Fish [1]	1.2 mg/l (96 h; Oncorhynchus mykiss; Lethal)
LC50 - Fish [2]	2.3 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
EC50 - Crustacea [1]	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	9.4 mg/l (EPA 660/3 - 75/009, Selenastrum capricornutum, Static system, Fresh water, Experimental value, Biomass)
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
Threshold limit - Algae [1]	> 11 mg/l (72 h; Scenedesmus sp.)
Threshold limit - Algae [2]	4.2 mg/l (72 h; Scenedesmus sp.)

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	

Trimethylol ethane triglycidyl ether Polymer (68460-21-9)	

butanedioldiglycidyl ether (2425-79-8)	
LC50 - Fish [1]	24 mg/l (96 h; Pisces) ECHA
LC50 - Other aquatic organisms [1]	> 160 mg/l
NOEC (acute)	40 mg/l

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

butanedioldiglycidyl ether (2425-79-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.15
Threshold limit - Algae [1]	88930 mg/l (96 h; Algae)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LC50 - Fish [1]	55 mg/l (96 h; Cyprinus carpio; Young)
LC50 - Fish [2]	237 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 - Crustacea [1]	473 – 710 mg/l (48 h; Daphnia magna)
Partition coefficient n-octanol/water (Log Pow)	-0.92 (Estimated value)
Threshold limit - Algae [1]	119 mg/l (7 days; Anabaena flosaquae)
Threshold limit - Algae [2]	250 mg/l (72 h; Selenastrum capricornutum)

12.2. Persistence and degradability

HIT-RE 500 V3, A	
Persistence and degradability	May cause long-term adverse effects in the environment.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Not rapidly degradable	

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
Not rapidly degradable	

butanedioldiglycidyl ether (2425-79-8)	
Biochemical oxygen demand (BOD)	0.01982 g O ₂ /g substance

12.3. Bioaccumulative potential

HIT-RE 500 V3, A	
Bioaccumulative potential	Not established.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).

butanedioldiglycidyl ether (2425-79-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.15

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.92 (Estimated value)

12.4. Mobility in soil

HIT-RE 500 V3, A	
Mobility in soil	No additional information available

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
Ecology - soil	No (test)data on mobility of the substance available.

butanedioldiglycidyl ether (2425-79-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.15

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.92 (Estimated value)

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
--	--

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
Special provision(s) applied : 375	Special provision(s) applied : 969	Special provision(s) applied : A197	Special provision(s) applied : 375

These substances when carried in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.

14.1. UN number or ID number

UN 3077	UN 3077	UN 3077	UN 3077
---------	---------	---------	---------

14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	Environmentally hazardous substance, solid, n.o.s. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)
---	---	---	---

Transport document description

UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III, (-)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III	UN 3077 Environmentally hazardous substance, solid, n.o.s. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane ; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III
--	---	---	---

14.3. Transport hazard class(es)

9	9	9	9

HIT-RE 500 V3, A


Safety Data Sheet

According to SS 586 Part 3: 2014

ADR	IMDG	IATA	RID
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
Environmentally hazardous substances derogation applies (quantity of liquids ≤ 5 litres or net mass of solids ≤ 5 kg). The environmentally hazardous substance mark is therefore not required, as stated in the ADR regulation, section 5.2.1.8.1.			
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	M7
Special provisions (ADR)	274, 335, 375, 601
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	

Tunnel restriction code (ADR) -

Transport by sea

Special provisions (IMDG)	274, 335, 966, 967, 969
Limited quantities (IMDG)	5 kg
Packing instructions (IMDG)	LP02, P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-F
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW23
MFAG-No	171

Air transport

PCA packing instructions (IATA)	956
PCA max net quantity (IATA)	400kg
CAO packing instructions (IATA)	956
Special provisions (IATA)	A97, A158, A179, A197, A215

Rail transport

Special provisions (RID)	274, 335, 375, 601
Limited quantities (RID)	5kg
Packing instructions (RID)	P002, IBC08, LP02, R001

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

15.2. International regulations

No additional information available

15.3 Chemical inventory status

No additional information available

SECTION 16: Other information

Issue date	08/12/2022
Revision date	08/12/2022
Abbreviations and acronyms	<p>ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways</p> <p>ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road</p> <p>ATE - Acute Toxicity Estimate</p> <p>BCF - Bioconcentration factor</p> <p>CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008</p> <p>DMEL - Derived Minimal Effect level</p> <p>DNEL - Derived-No Effect Level</p> <p>IATA - International Air Transport Association</p> <p>EC50 - Median effective concentration</p> <p>IMDG - International Maritime Dangerous Goods</p> <p>LC50 - Median lethal concentration</p> <p>LD50 - Median lethal dose</p> <p>LOAEL - Lowest Observed Adverse Effect Level</p> <p>NOAEC - No-Observed Adverse Effect Concentration</p> <p>NOAEL - No-Observed Adverse Effect Level</p> <p>NOEC - No-Observed Effect Concentration</p> <p>PBT - Persistent Bioaccumulative Toxic</p> <p>PNEC - Predicted No-Effect Concentration</p> <p>REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006</p> <p>RID - Regulations concerning the International Carriage of Dangerous Goods by Rail</p> <p>SDS - Safety Data Sheet</p> <p>vPvB - Very Persistent and Very Bioaccumulative</p>
Other information	None.

Indication of changes			
Section	Changed item	Change	Comments
14	Transportation information	Modified	
2	GHS SG classification	Modified	
2	Hazard pictograms (GHS SG)	Modified	
2	Hazard statements (GHS SG)	Modified	
3	Composition/information on ingredients	Modified	

SDS_SG_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014
Issue date: 08.12.2022

Revision date: 08.12.2022

Supersedes: 13.05.2020

Version: 1.5

SECTION 1: Identification

1.1. Product identifier

Name HIT-RE 500 V3, B
Product code BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended uses and restrictions For professional use only
Recommended use Composite mortar component for fasteners in the construction industry

1.4. Supplier's details

Supplier

Hilti Far East Private Ltd.
80 Pasir Panjang Road, #16-83/84 Mapletree Business City Singapore
Singapur 117372
T +65 6777 7887 - F +65 6777 3057
sg-customerservice@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6 Kaufering Deutschland 86916
T +49 8191 906876
anchor.hse@hilti.com

1.5. Emergency phone number

Emergency number Schweizerisches Toxikologisches Informationszentrum – 24h Service
+41 44 251 51 51 (international)
+65 6777 7887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Health hazards Skin corrosion/irritation, Category 1B
Skin sensitisation, Category 1
Specific target organ toxicity – Single exposure, Category 3

2.2. GHS label elements including precautionary statements

Hazard pictograms (GHS SG)



Signal word (GHS SG)

Danger

Hazard statements (GHS SG)

H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.
H335 : May cause respiratory irritation.

Precautionary statements

Prevention

P280 : Wear eye protection, protective clothing, protective gloves.
P262 : Do not get in eyes, on skin, or on clothing.

Response

P305+P351+P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 : If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 : If eye irritation persists: Get medical advice/attention.
P302+P352 : IF ON SKIN: Wash with plenty of soap and water.

2.3. Other hazards which do not result in classification

No additional information available

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Synonyms	Concentration (%)	Formula	Product identifier
2-methyl-1,5-pentanediamine	1,5-diamino-2-methylpentane / 1,5-pentanediamine, 2-methyl-	25 – 35	C6H16N2	CAS-No.: 15520-10-2 EC-No.: 239-556-6
Phenol, styrenated	Phenol, styrenated / Wingstay S	5 – 10	-	CAS-No.: 61788-44-1 EC-No.: 262-975-0
m-Xylylenediamine	-	5 – <8	C8H12N2	CAS-No.: 1477-55-0 EC-No.: 216-032-5
2,4,6-tris(dimethylaminomethyl)phenol	2,4,6-tris(dimethylaminomethyl)phenol / tris-2,4,6-(dimethylaminomethyl)phenol	1 – 2.5	C15H27N3O	CAS-No.: 90-72-2 EC-No.: 202-013-9 EC Index-No.: 603-069-00-0
3-Aminopropyltriethoxysilan	-	1 – 2.5	C9H23NO3Si	CAS-No.: 919-30-2 EC-No.: 213-048-4 EC Index-No.: 612-108-00-0

SECTION 4: First-aid measures

4.1. Description of necessary first aid measures

First-aid measures general

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation

Remove person to fresh air and keep comfortable for breathing.

Skin contact

Wash with plenty of water/.... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.

Eye contact

Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.

Ingestion

Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects

Causes severe skin burns and eye damage.

Symptoms/effects after skin contact

May cause an allergic skin reaction.

Symptoms/effects after eye contact

Causes serious eye damage.

4.3. Indication of immediate medical attention and special treatment needed

Other medical advice or treatment

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media

Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media

Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire

Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

5.3. Special protective actions for fire fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
6.1.1. For non-emergency personnel	
Emergency procedures	Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact during pregnancy/while nursing.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	Comply with applicable regulations.
Storage conditions	Protect from sunlight. Store in a well-ventilated place.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 – 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters/Occupational exposure limits

No additional information available

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

8.2. Monitoring

No additional information available

8.3. Appropriate engineering control measures

Appropriate engineering controls Ensure good ventilation of the work station.

8.4. Personal protection

Materials for protective clothing Long sleeved protective clothing
 Hand protection Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN ISO 374

Eye protection Wear security glasses which protect from splashes

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Personal protective equipment symbol(s)



Environmental exposure controls No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.
 Consumer exposure controls Avoid contact during pregnancy/while nursing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	red
Odour	Amine-like
Odour threshold	No data available
pH	11.5
Relative evaporation rate (butylacetate=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	1.31 g/cm ³
Solubility	insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	No data available
Partition coefficient n-octanol/water (Log Kow)	No data available
Viscosity, dynamic	50 – 70 Pa·s HN-0333
Explosive properties	No data available
Oxidising properties	No data available
Explosive limits	No data available

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive vapours.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide. Corrosive vapours.

SECTION 11: Toxicological information

11.1. Acute toxicity

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2-methyl-1,5-pentanediamine (15520-10-2)	
LD50 oral rat	1690 mg/kg (Rat)
LD50 dermal rat	1870 mg/kg
LC50 Inhalation - Rat	4.9 mg/l
Phenol, styrenated (61788-44-1)	
LD50 oral rat	> 2500 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	158.31 mg/l/4h
m-Xylylenediamine (1477-55-0)	
LD50 oral rat	1090 mg/kg
LD50 dermal rat	> 3100 mg/kg
LD50 dermal	> 3100 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	1.34 mg/l/4h
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LD50 oral rat	2169 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)
3-Aminopropyltriethoxysilan (919-30-2)	
LD50 oral rat	1.57 – 2.83 ml/kg (EPA OTS 798.1175, Rat, Male / female, Experimental value, Oral)

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

3-Aminopropyltriethoxysilan (919-30-2)	
LD50 dermal rabbit	4.29 ml/kg (EPA OTS 798.1100, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat [ppm]	> 5 ppm (OECD 403: Acute Inhalation Toxicity, 6 h, Rat, Male, Experimental value, Inhalation (vapours))

Skin corrosion/irritation	Causes severe skin burns. pH: 11.5
Serious eye damage/irritation	Assumed to cause serious eye damage
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	May cause respiratory irritation.

2-methyl-1,5-pentanediamine (15520-10-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-RE 500 V3, B	
Density	1.31 g/cm ³
Potential adverse human health effects and symptoms	No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
Other information	Avoid release to the environment.

2-methyl-1,5-pentanediamine (15520-10-2)	
LC50 - Fish [1]	130 mg/l (LC50; 48 h)
LOEC (acute)	1800 mg/l
NOEC (acute)	1000 mg/l
Partition coefficient n-octanol/water (Log Pow)	0.27 (Estimated value)

Phenol, styrenated (61788-44-1)	
LC50 - Fish [1]	5.6 mg/l
LC50 - Other aquatic organisms [1]	9.7 mg/l
EC50 - Crustacea [1]	1.44 mg/l
EC50 72h - Algae [1]	0.326 mg/l (Algae, Literature study)
NOEC (acute)	3.2 mg/l
BCF - Fish [1]	3246 l/kg (BCFBAF v3.01, Pisces, Fresh water, Weight of evidence, Fresh weight)
BCF - Fish [2]	3246 mg/l
Partition coefficient n-octanol/water (Log Pow)	6.24 – 7.77 (Experimental value; OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

Phenol, styrenated (61788-44-1)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.145 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Threshold limit - Algae [1]	0.326 mg/l (72 h; Algae)
Threshold limit - Algae [2]	0.14 mg/l (72 h; Algae)
m-Xylylenediamine (1477-55-0)	
LC50 - Fish [1]	75 mg/l
LC50 - Other aquatic organisms [1]	20.3 ppb
EC50 - Crustacea [1]	15 mg/l
LOEC (chronic)	15 mg/l
NOEC (acute)	10.5 mg/kg
NOEC (chronic)	4.7 mg/l
NOEC chronic crustacea	4.7 mg/l
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 - Fish [1]	> 100 mg/l (96 h; Pisces; Nominal concentration)
LC50 - Fish [2]	70.9 mg/l (96 h; Pisces)
EC50 - Other aquatic organisms [1]	84 mg/l (72 h; Desmodesmus subspicatus; growth rate; ECHA)
ErC50 algae	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	2 mg/l (28 d; activated sludge, domestic; respiration rate; ECHA)
Partition coefficient n-octanol/water (Log Pow)	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.32 (log Koc, Calculated value)
Threshold limit - Algae [1]	10 - 100, Algae
Threshold limit - Algae [2]	84 mg/l (72 h; Scenedesmus subspicatus; Growth rate)
3-Aminopropyltriethoxysilan (919-30-2)	
LC50 - Fish [1]	> 934 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	331 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	> 1000 mg/l (EU Method C.3, 72 h, Scenedesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
BCF - Fish [1]	3.4 (OECD 305: Bioconcentration: Flow-Through Fish Test, 8 week(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	1.7 (QSAR, 20 °C)
12.2. Persistence and degradability	
HIT-RE 500 V3, B	
Persistence and degradability	May cause long-term adverse effects in the environment.
Phenol, styrenated (61788-44-1)	
Biochemical oxygen demand (BOD)	0.000231 g O ₂ /g substance

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

Phenol, styrenated (61788-44-1)	
Chemical oxygen demand (COD)	0.004827 g O ₂ /g substance
m-Xylylenediamine (1477-55-0)	
Not rapidly degradable	
3-Aminopropyltriethoxysilan (919-30-2)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

HIT-RE 500 V3, B	
Bioaccumulative potential	Not established.
2-methyl-1,5-pentanediamine (15520-10-2)	
Partition coefficient n-octanol/water (Log Pow)	0.27 (Estimated value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Phenol, styrenated (61788-44-1)	
BCF - Fish [1]	3246 l/kg (BCFBAF v3.01, Pisces, Fresh water, Weight of evidence, Fresh weight)
BCF - Fish [2]	3246 mg/l
Partition coefficient n-octanol/water (Log Pow)	6.24 – 7.77 (Experimental value; OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.145 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Bioaccumulative potential	Bioaccumulative potential.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Pow)	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.32 (log Koc, Calculated value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
3-Aminopropyltriethoxysilan (919-30-2)	
BCF - Fish [1]	3.4 (OECD 305: Bioconcentration: Flow-Through Fish Test, 8 week(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	1.7 (QSAR, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

HIT-RE 500 V3, B	
Mobility in soil	No additional information available
2-methyl-1,5-pentanediamine (15520-10-2)	
Partition coefficient n-octanol/water (Log Pow)	0.27 (Estimated value)
Phenol, styrenated (61788-44-1)	
Partition coefficient n-octanol/water (Log Pow)	6.24 – 7.77 (Experimental value; OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.145 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Pow)	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.32 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.
3-Aminopropyltriethoxysilan (919-30-2)	
Partition coefficient n-octanol/water (Log Pow)	1.7 (QSAR, 20 °C)
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
--	--

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number			
UN 3259	UN 3259	UN 3259	UN 3259
14.2. UN proper shipping name			
AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)
Transport document description			
UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II, (E)	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II
14.3. Transport hazard class(es)			
8	8	8	8
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

ADR	IMDG	IATA	RID
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	C8
Special provisions (ADR)	274
Limited quantities (ADR)	1kg
Packing instructions (ADR)	P002, IBC08
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	2
Orange plates	

Tunnel restriction code (ADR)	E
-------------------------------	---

Transport by sea

Special provisions (IMDG)	274
Limited quantities (IMDG)	1 kg
Packing instructions (IMDG)	P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A
MFAG-No	154

Air transport

PCA packing instructions (IATA)	859
PCA max net quantity (IATA)	15kg
CAO packing instructions (IATA)	863
Special provisions (IATA)	A3

Rail transport

Special provisions (RID)	274
Limited quantities (RID)	1kg
Packing instructions (RID)	P002, IBC08

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

15.2. International regulations

No additional information available

15.3 Chemical inventory status

No additional information available

SECTION 16: Other information

Issue date	08/12/2022
Revision date	08/12/2022

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE - Acute Toxicity Estimate
BCF - Bioconcentration factor
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL - Derived Minimal Effect level
DNEL - Derived-No Effect Level
IATA - International Air Transport Association
EC50 - Median effective concentration
IMDG - International Maritime Dangerous Goods
LC50 - Median lethal concentration
LD50 - Median lethal dose
LOAEL - Lowest Observed Adverse Effect Level
NOAEC - No-Observed Adverse Effect Concentration
NOAEL - No-Observed Adverse Effect Level
NOEC - No-Observed Effect Concentration
PBT - Persistent Bioaccumulative Toxic
PNEC - Predicted No-Effect Concentration
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS - Safety Data Sheet
vPvB - Very Persistent and Very Bioaccumulative
None.

Other information

SDS_SG_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-RE 500 V3

Safety information for 2-Component-products

Issue date: 13/05/2020

Revision date: 13/05/2020

Supersedes: 26/02/2019

Version: 2.3

SECTION 1: Kit identification

1.1 Product identifier

Trade name

HIT-RE 500 V3



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti Far East Private Ltd.
80 Pasir Panjang Road,
#16-83/84 Mapletree Business City
117372 Singapore - Singapur
T +65 6777 7887 - F +65 6777 3057
sg-customerservice@hilti.com

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3: Kit contents

Classification of the Product

GHS SG classification

Health hazards

Skin corrosion/irritation, Category 1B
Serious eye damage/eye irritation, Category 1
Skin sensitisation, Category 1
Germ cell mutagenicity, Category 2
Reproductive toxicity, Category 1B

Environmental hazards

Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
Hazardous to the aquatic environment – Chronic Hazard, Category 2

Label elements

GHS SG labelling

Hazard pictograms (GHS SG)



GHS05



GHS07



GHS08



GHS09

Signal word (GHS SG)

Danger

Hazardous ingredients

Epoxy resin, Amines

Hazard statements (GHS SG)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.

HIT-RE 500 V3

Safety information for 2-Component-products


Precautionary statements (GHS SG)

H335 - May cause respiratory irritation.
 H341 - Suspected of causing genetic defects.
 H360 - May damage fertility or the unborn child.
 H411 - Toxic to aquatic life with long lasting effects.

P280 - Wear eye protection, protective clothing, protective gloves.
 P262 - Do not get in eyes, on skin, or on clothing.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P302+P352 - IF ON SKIN: Wash with plenty of water.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

Additional information

2-component-foilpack, contains:
 Component A: Epoxy resin, Reactive diluent, inorganic filler
 Component B: Amine hardener, inorganic filler



Name	General description	Quantity	Unit	GHS SG classification
HIT-RE 500 V3, B		1	pcs (pieces)	Acute Tox. 5 (Oral), H303 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
HIT-RE 500 V3, A (GHS08)		1	pcs (pieces)	Skin Corr. 1C, H314 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

SECTION 4: General advice

General advice For professional users only

SECTION 5: Safe handling advice

General measures Spilled material may present a slipping hazard

Environmental precautions Prevent entry to sewers and public waters
 Notify authorities if liquid enters sewers or public waters
 Avoid release to the environment
 Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations.
 After curing, the product can be disposed of with household waste.

Storage conditions Protect from sunlight. Store in a well-ventilated place.

Technical measures Comply with applicable regulations

Precautions for safe handling Wear personal protective equipment
 Avoid contact with skin and eyes
 Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work
 Avoid contact during pregnancy/while nursing

Methods for cleaning up This material and its container must be disposed of in a safe way, and as per local legislation
 Mechanically recover the product
 On land, sweep or shovel into suitable containers
 Store away from other materials.

For containment Collect spillage.

HIT-RE 500 V3

Safety information for 2-Component-products

Incompatible materials	Sources of ignition Direct sunlight
Incompatible products	Strong bases Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist
First-aid measures after ingestion	Do not induce vomiting Rinse mouth Immediately call a POISON CENTER/doctor.
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	Wash with plenty of water/... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures general	Never give anything by mouth to an unconscious person If you feel unwell, seek medical advice (show the label where possible)
Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after eye contact	Causes serious eye damage.
Symptoms/effects after skin contact	May cause an allergic skin reaction.

SECTION 7: Fire fighting measures

Firefighting instructions	Use water spray or fog for cooling exposed containers Exercise caution when fighting any chemical fire Prevent fire fighting water from entering the environment
Protection during firefighting	Self-contained breathing apparatus Do not enter fire area without proper protective equipment, including respiratory protection
Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide Carbon monoxide

SECTION 8: Other information

No data available

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014
Issue date: 08.12.2022

Revision date: 08.12.2022

Supersedes: 13.05.2020

Version: 1.5

SECTION 1: Identification

1.1. Product identifier

Name HIT-RE 500 V3, B
Product code BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use Composite mortar component for fasteners in the construction industry

1.4. Supplier's details

Supplier

Hilti Far East Private Ltd.
80 Pasir Panjang Road, #16-83/84 Mapletree Business City Singapore
Singapur 117372
T +65 6777 7887 - F +65 6777 3057
sg-customerservice@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6 Kaufering Deutschland 86916
T +49 8191 906876
anchor.hse@hilti.com

1.5. Emergency phone number

Emergency number GBK GmbH Global Regulatory Compliance
+49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Health hazards Skin corrosion/irritation, Category 1B
Skin sensitisation, Category 1
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

2.2. GHS label elements including precautionary statements

Hazard pictograms (GHS SG)



Signal word (GHS SG)

Danger

Hazard statements (GHS SG)

H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.
H335 : May cause respiratory irritation.

Precautionary statements

Prevention

P280 : Wear eye protection, protective clothing, protective gloves.
P262 : Do not get in eyes, on skin, or on clothing.

Response

P305+P351+P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 : If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 : If eye irritation persists: Get medical advice/attention.
P302+P352 : IF ON SKIN: Wash with plenty of soap and water.

2.3. Other hazards which do not result in classification

No additional information available

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Synonyms	Concentration (%)	Formula	Product identifier
2-methyl-1,5-pentanediamine	1,5-diamino-2-methylpentane / 1,5-pentanediamine, 2-methyl-	25 – 35	C6H16N2	CAS-No.: 15520-10-2 EC-No.: 239-556-6
Phenol, styrenated	Phenol, styrenated / Wingstay S	5 – 10	-	CAS-No.: 61788-44-1 EC-No.: 262-975-0
m-Xylylenediamine	-	5 – <8	C8H12N2	CAS-No.: 1477-55-0 EC-No.: 216-032-5
2,4,6-tris(dimethylaminomethyl)phenol	2,4,6-tris(dimethylaminomethyl)phenol / tris-2,4,6-(dimethylaminomethyl)phenol	1 – 2.5	C15H27N3O	CAS-No.: 90-72-2 EC-No.: 202-013-9 EC Index-No.: 603-069-00-0
3-Aminopropyltriethoxysilan	-	1 – 2.5	C9H23NO3Si	CAS-No.: 919-30-2 EC-No.: 213-048-4 EC Index-No.: 612-108-00-0

SECTION 4: First-aid measures

4.1. Description of necessary first aid measures

First-aid measures general

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation

Remove person to fresh air and keep comfortable for breathing.

Skin contact

Wash with plenty of water/.... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.

Eye contact

Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.

Ingestion

Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects

Causes severe skin burns and eye damage.

Symptoms/effects after skin contact

May cause an allergic skin reaction.

Symptoms/effects after eye contact

Causes serious eye damage.

4.3. Indication of immediate medical attention and special treatment needed

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media

Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media

Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire

Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

5.3. Special protective actions for fire fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
6.1.1. For non-emergency personnel	
Emergency procedures	Evacuate unnecessary personnel.
6.1.2. For emergency responders	
Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.
Other information	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact during pregnancy/while nursing.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	Comply with applicable regulations.
Storage conditions	Protect from sunlight. Store in a well-ventilated place.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 – 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters/Occupational exposure limits

No additional information available

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

8.2. Monitoring

No additional information available

8.3. Appropriate engineering control measures

Appropriate engineering controls

Ensure good ventilation of the work station.

8.4. Personal protection

Materials for protective clothing

Long sleeved protective clothing

Hand protection

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN ISO 374

Eye protection

Wear security glasses which protect from splashes

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Personal protective equipment symbol(s)



Environmental exposure controls

No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.

Consumer exposure controls

Avoid contact during pregnancy/while nursing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	red
Odour	Amine-like
Odour threshold	No data available
pH	11.5
Relative evaporation rate (butylacetate=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	Not applicable
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	1.31 g/cm ³
Solubility	insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	No data available
Partition coefficient n-octanol/water (Log Kow)	No data available
Viscosity, dynamic	50 – 70 Pa·s HN-0333
Explosive properties	No data available
Oxidising properties	No data available
Explosive limits	No data available

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive vapours.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide. Corrosive vapours.

SECTION 11: Toxicological information

11.1. Acute toxicity

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2-methyl-1,5-pentanediamine (15520-10-2)	
LD50 oral rat	1690 mg/kg (Rat)
LD50 oral	1170 mg/kg (Rat)
LC50 Inhalation - Rat	4.9 mg/l
Phenol, styrenated (61788-44-1)	
LD50 oral rat	> 2500 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	158.31 mg/l/4h
m-Xylylenediamine (1477-55-0)	
LD50 oral rat	930 mg/kg
LD50 dermal rat	> 3100 mg/kg
LD50 dermal	> 3100 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	1.34 mg/l/4h
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LD50 oral rat	2169 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)
3-Aminopropyltriethoxysilan (919-30-2)	
LD50 oral rat	1.57 – 2.83 ml/kg (EPA OTS 798.1175, Rat, Male / female, Experimental value, Oral)

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

3-Aminopropyltriethoxysilan (919-30-2)	
LD50 oral	1570 mg/kg
LD50 dermal rabbit	4.29 ml/kg (EPA OTS 798.1100, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LD50 dermal	4290 mg/kg
LC50 Inhalation - Rat [ppm]	> 5 ppm (OECD 403: Acute Inhalation Toxicity, 6 h, Rat, Male, Experimental value, Inhalation (vapours))
LC50 Inhalation - Rat (Dust/Mist)	7.35 mg/l/4h
Skin corrosion/irritation	Causes severe skin burns. pH: 11.5
Serious eye damage/irritation	Assumed to cause serious eye damage
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	May cause respiratory irritation.
2-methyl-1,5-pentanediamine (15520-10-2)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
HIT-RE 500 V3, B	
Density	1.31 g/cm ³
Potential adverse human health effects and symptoms	No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified
Other information	Avoid release to the environment.

2-methyl-1,5-pentanediamine (15520-10-2)	
LC50 - Fish [1]	130 mg/l (LC50; 48 h)
LOEC (acute)	1800 mg/l
NOEC (acute)	1000 mg/l
Partition coefficient n-octanol/water (Log Pow)	0.27 (Estimated value)
Phenol, styrenated (61788-44-1)	
LC50 - Fish [1]	5.6 mg/l
LC50 - Other aquatic organisms [1]	9.7 mg/l
EC50 - Crustacea [1]	1.44 mg/l
EC50 72h - Algae [1]	0.326 mg/l (Algae, Literature study)
NOEC (acute)	3.2 mg/l
BCF - Fish [1]	3246 l/kg (BCFBAF v3.01, Pisces, Fresh water, Weight of evidence, Fresh weight)

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

Phenol, styrenated (61788-44-1)	
BCF - Fish [2]	3246 mg/l
Partition coefficient n-octanol/water (Log Pow)	6.24 – 7.77 (Experimental value; OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.145 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Threshold limit - Algae [1]	0.326 mg/l (72 h; Algae)
Threshold limit - Algae [2]	0.14 mg/l (72 h; Algae)
m-Xylylenediamine (1477-55-0)	
LC50 - Fish [1]	75 mg/l
LC50 - Other aquatic organisms [1]	20.3 ppb
EC50 - Crustacea [1]	15 mg/l
LOEC (chronic)	15 mg/l
NOEC (acute)	10.5 mg/kg
NOEC (chronic)	4.7 mg/l
NOEC chronic crustacea	4.7 mg/l
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 - Fish [1]	> 100 mg/l (96 h; Pisces; Nominal concentration)
LC50 - Fish [2]	70.9 mg/l (96 h; Pisces)
EC50 - Other aquatic organisms [1]	84 mg/l (72 h; Desmodesmus subspicatus; growth rate; ECHA)
ErC50 algae	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	2 mg/l (28 d; activated sludge, domestic; respiration rate; ECHA)
Partition coefficient n-octanol/water (Log Pow)	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.32 (log Koc, Calculated value)
Threshold limit - Algae [1]	10 - 100, Algae
Threshold limit - Algae [2]	84 mg/l (72 h; Scenedesmus subspicatus; Growth rate)
3-Aminopropyltriethoxysilan (919-30-2)	
LC50 - Fish [1]	> 934 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	331 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	> 1000 mg/l (EU Method C.3, 72 h, Scenedesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
BCF - Fish [1]	3.4 (OECD 305: Bioconcentration: Flow-Through Fish Test, 8 week(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	1.7 (QSAR, 20 °C)

12.2. Persistence and degradability

HIT-RE 500 V3, B	
Persistence and degradability	May cause long-term adverse effects in the environment.

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

Phenol, styrenated (61788-44-1)	
Biochemical oxygen demand (BOD)	0.000231 g O ₂ /g substance
Chemical oxygen demand (COD)	0.004827 g O ₂ /g substance
m-Xylylenediamine (1477-55-0)	
Not rapidly degradable	
3-Aminopropyltriethoxysilan (919-30-2)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

HIT-RE 500 V3, B	
Bioaccumulative potential	Not established.
2-methyl-1,5-pentanediamine (15520-10-2)	
Partition coefficient n-octanol/water (Log Pow)	0.27 (Estimated value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Phenol, styrenated (61788-44-1)	
BCF - Fish [1]	3246 l/kg (BCFBAF v3.01, Pisces, Fresh water, Weight of evidence, Fresh weight)
BCF - Fish [2]	3246 mg/l
Partition coefficient n-octanol/water (Log Pow)	6.24 – 7.77 (Experimental value; OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.145 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Bioaccumulative potential	Bioaccumulative potential.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Partition coefficient n-octanol/water (Log Pow)	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.32 (log Koc, Calculated value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
3-Aminopropyltriethoxysilan (919-30-2)	
BCF - Fish [1]	3.4 (OECD 305: Bioconcentration: Flow-Through Fish Test, 8 week(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	1.7 (QSAR, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

HIT-RE 500 V3, B	
Mobility in soil	No additional information available
2-methyl-1,5-pentanediamine (15520-10-2)	
Partition coefficient n-octanol/water (Log Pow)	0.27 (Estimated value)
Phenol, styrenated (61788-44-1)	
Partition coefficient n-octanol/water (Log Pow)	6.24 – 7.77 (Experimental value; OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

Phenol, styrenated (61788-44-1)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.145 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Pow)	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.32 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.
3-Aminopropyltriethoxysilan (919-30-2)	
Partition coefficient n-octanol/water (Log Pow)	1.7 (QSAR, 20 °C)
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
--	--

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
UN 3259	UN 3259	UN 3259	UN 3259
14.2. UN proper shipping name			
AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)
Transport document description			
UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II, (E)	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II
14.3. Transport hazard class(es)			
8	8	8	8

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

ADR	IMDG	IATA	RID
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	C8
Special provisions (ADR)	274
Limited quantities (ADR)	1kg
Packing instructions (ADR)	P002, IBC08
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	2
Orange plates	



Tunnel restriction code (ADR)	E
-------------------------------	---

Transport by sea

Special provisions (IMDG)	274
Limited quantities (IMDG)	1 kg
Packing instructions (IMDG)	P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A
MFAG-No	154

Air transport

PCA packing instructions (IATA)	859
PCA max net quantity (IATA)	15kg
CAO packing instructions (IATA)	863
Special provisions (IATA)	A3

Rail transport

Special provisions (RID)	274
Limited quantities (RID)	1kg
Packing instructions (RID)	P002, IBC08

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

HIT-RE 500 V3, B

Safety Data Sheet

According to SS 586 Part 3: 2014

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

15.2. International regulations

No additional information available

15.3 Chemical inventory status

No additional information available

SECTION 16: Other information

Issue date	08/12/2022
Revision date	08/12/2022
Abbreviations and acronyms	ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road ATE - Acute Toxicity Estimate BCF - Bioconcentration factor CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 DMEL - Derived Minimal Effect level DNEL - Derived-No Effect Level IATA - International Air Transport Association EC50 - Median effective concentration IMDG - International Maritime Dangerous Goods LC50 - Median lethal concentration LD50 - Median lethal dose LOAEL - Lowest Observed Adverse Effect Level NOAEC - No-Observed Adverse Effect Concentration NOAEL - No-Observed Adverse Effect Level NOEC - No-Observed Effect Concentration PBT - Persistent Bioaccumulative Toxic PNEC - Predicted No-Effect Concentration REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail SDS - Safety Data Sheet vPvB - Very Persistent and Very Bioaccumulative
Other information	None.

SDS_SG_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014
Issue date: 13.05.2020

Revision date: 13.05.2020

Supersedes: 26.02.2019

Version: 2.3

SECTION 1: Identification

1.1. Product identifier

Name HIT-RE 500 V3, A (GHS08)
Product code BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use Composite mortar component for fasteners in the construction industry

1.4. Supplier's details

Hilti Far East Private Ltd.
80 Pasir Panjang Road, #16-83/84 Mapletree Business City Singapore Singapur 117372
T +65 6777 7887 - F +65 6777 3057
sg-customerservice@hilti.com

1.5. Emergency phone number

Emergency number GBK GmbH Global Regulatory Compliance
+49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Health hazards Skin corrosion/irritation, Category 1C
Skin sensitisation, Category 1
Germ cell mutagenicity, Category 2
Reproductive toxicity, Category 1B
Environmental hazards Hazardous to the aquatic environment – Chronic Hazard, Category 2

2.2. GHS label elements including precautionary statements

Hazard pictograms (GHS SG)



Signal word (GHS SG)

Danger

Hazard statements (GHS SG)

H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.
H341 : Suspected of causing genetic defects.
H360 : May damage fertility or the unborn child.
H411 : Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P280 : Wear eye protection, protective clothing, protective gloves.
P262 : Do not get in eyes, on skin, or on clothing.

Response

P305+P351+P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 : If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 : If eye irritation persists: Get medical advice/attention.
P302+P352 : IF ON SKIN: Wash with plenty of soap and water.

2.3. Other hazards which do not result in classification

No additional information available

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Synonyms	Concentration (%)	Formula	Product identifier
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane / 2,2-bis(4-(2,3-epoxypropyloxy)phenyl)propane / 2,2-bis(4-glycidyoxyphenyl)propane	25 – 40	C ₂₁ H ₂₄ O ₄	CAS-No.: 1675-54-3 EC-No.: 216-823-5
butanedioldiglycidyl ether	1,4-bis(2,3-epoxypropoxy)butane / 1,4-bis(2,3-epoxypropyloxy)butane / 1,4-bis(glycidyoxy)butane	5 – 10	C ₁₀ H ₁₈ O ₄	CAS-No.: 2425-79-8 EC-No.: 219-371-7 EC Index-No.: 603-072-00-7
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	((3-(trimethoxysilyl)propoxy)methyl)oxirane / [3-(2,3-epoxypropoxy)propyl]trimethoxysilane / 1-(glycidyoxy)-3-(trimethoxysilyl)propane	2.5 – 5	C ₉ H ₂₀ O ₅ Si	CAS-No.: 2530-83-8 EC-No.: 219-784-2

SECTION 4: First-aid measures

4.1. Description of necessary first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
Inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
Skin contact	Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get immediate medical advice/attention.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
Ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after skin contact	Causes skin irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye irritation.

4.3. Indication of immediate medical attention and special treatment needed

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Special protective actions for fire fighters

Firefighting instructions Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment Use personal protective equipment as required. Equip cleanup crew with proper protection.

Emergency procedures Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

6.3. Methods and material for containment and cleaning up

For containment Collect spillage.

Methods for cleaning up This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.

Other information Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene measures Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions Protect from sunlight.

Incompatible products Strong bases. Strong acids.

Incompatible materials Sources of ignition. Direct sunlight.

Storage temperature 5 – 25 °C

Heat and ignition sources Keep away from heat and direct sunlight.

7.3. Specific end use(s)

No additional information available

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

SECTION 8: Exposure controls/personal protection

8.1. Control parameters/Occupational exposure limits

HIT-RE 500 V3, A	
Singapore - Occupational Exposure Limits	
PEL (OEL TWA)	0.1 mg/m ³ Quartz, respirable dust

8.2. Monitoring

No additional information available

8.3. Appropriate engineering control measures

Appropriate engineering controls No specific measures identified.

8.4. Personal protection

Materials for protective clothing Long sleeved protective clothing
 Hand protection Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN ISO 374

Eye protection Wear security glasses which protect from splashes

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Personal protective equipment symbol(s)



Environmental exposure controls

No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.

Consumer exposure controls

Avoid contact during pregnancy/while nursing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Light grey
Odour	characteristic
Odour threshold	No data available
pH	6.6
Relative evaporation rate (butylacetate=1)	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	Not applicable
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability	Non flammable.
Vapour pressure	No data available
Relative vapour density at 20°C	No data available
Relative density	No data available
Density	1.45 g/cm ³

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

Solubility	insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	No data available
Partition coefficient n-octanol/water (Log Kow)	No data available
Viscosity, dynamic	45 – 59 Pa·s 23 °C
Explosive properties	No data available
Oxidising properties	No data available
Explosive limits	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Acute toxicity

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Experimental value)
LD50 oral	11400 mg/kg
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
butanedioldiglycidyl ether (2425-79-8)	
LD50 oral rat	2980 mg/kg (Rat)
LD50 oral	1163 mg/kg (Rat; Exp. Key study ECHA)
LD50 dermal rat	> 2150 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rat, Male / female, Experimental value, Dermal, 7 day(s))
LD50 dermal rabbit	1130 mg/kg (Rabbit)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LD50 oral rat	8025 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	4250 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

Skin corrosion/irritation	Causes severe skin burns. pH: 6.6
Serious eye damage/irritation	Assumed to cause serious eye damage
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Suspected of causing genetic defects.
Carcinogenicity	Not classified
Reproductive toxicity	May damage fertility or the unborn child.
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

HIT-RE 500 V3, A	
Density	1.45 g/cm ³
Potential adverse human health effects and symptoms	No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Toxic to aquatic life with long lasting effects.
Other information	Avoid release to the environment.

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LC50 - Fish [1]	1.2 mg/l (96 h; Oncorhynchus mykiss; Lethal)
LC50 - Fish [2]	2.3 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
EC50 - Crustacea [1]	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	9.4 mg/l (EPA 660/3 - 75/009, Selenastrum capricornutum, Static system, Fresh water, Experimental value, Biomass)
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
Threshold limit - Algae [1]	> 11 mg/l (72 h; Scenedesmus sp.)
Threshold limit - Algae [2]	4.2 mg/l (72 h; Scenedesmus sp.)

butanedioldiglycidyl ether (2425-79-8)	
LC50 - Fish [1]	24 mg/l (96 h; Pisces) ECHA
LC50 - Other aquatic organisms [1]	> 160 mg/l
NOEC (acute)	40 mg/l
Partition coefficient n-octanol/water (Log Pow)	-0.27 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.1 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Threshold limit - Algae [1]	88930 mg/l (96 h; Algae)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LC50 - Fish [1]	55 mg/l (96 h; Cyprinus carpio; Young)

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LC50 - Fish [2]	237 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 - Crustacea [1]	473 – 710 mg/l (48 h; Daphnia magna)
Partition coefficient n-octanol/water (Log Pow)	-0.92 (Estimated value)
Threshold limit - Algae [1]	119 mg/l (7 days; Anabaena flosaquae)
Threshold limit - Algae [2]	250 mg/l (72 h; Selenastrum capricornutum)

12.2. Persistence and degradability

HIT-RE 500 V3, A	
Persistence and degradability	May cause long-term adverse effects in the environment.
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Not rapidly degradable	
butanedioldiglycidyl ether (2425-79-8)	
Biochemical oxygen demand (BOD)	0.01982 g O ₂ /g substance

12.3. Bioaccumulative potential

HIT-RE 500 V3, A	
Bioaccumulative potential	Not established.
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).
butanedioldiglycidyl ether (2425-79-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.27 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.1 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.92 (Estimated value)

12.4. Mobility in soil

HIT-RE 500 V3, A	
Mobility in soil	No additional information available
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
Ecology - soil	No (test) data on mobility of the substance available.
butanedioldiglycidyl ether (2425-79-8)	
Surface tension	44.4 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Pow)	-0.27 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.1 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

butanedioldiglycidyl ether (2425-79-8)	
Ecology - soil	Highly mobile in soil.
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Partition coefficient n-octanol/water (Log Pow)	-0.92 (Estimated value)

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
--	--

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
UN 1759	UN 1759	UN 1759	UN 1759
14.2. UN proper shipping name			
CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)	CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)	Corrosive solid, n.o.s. (trimethylolpropane triglycidylether)	CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)
Transport document description			
UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, (E), ENVIRONMENTALLY HAZARDOUS	UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1759 Corrosive solid, n.o.s. (trimethylolpropane triglycidylether), 8, III, ENVIRONMENTALLY HAZARDOUS	UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)			
8	8	8	8
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available			

HIT-RE 500 V3, A


Safety Data Sheet

According to SS 586 Part 3: 2014

14.6. Special precautions for user

Overland transport

Classification code (ADR)	C10
Special provisions (ADR)	274
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	



Tunnel restriction code (ADR)	E
-------------------------------	---

Transport by sea

Special provisions (IMDG)	223, 274
Packing instructions (IMDG)	P002, LP02
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A

Air transport

PCA packing instructions (IATA)	860
PCA max net quantity (IATA)	25kg
CAO packing instructions (IATA)	864
Special provisions (IATA)	A3, A803

Rail transport

Special provisions (RID)	274
Packing instructions (RID)	P002, IBC08, LP02, R001

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

15.2. International regulations

No additional information available

15.3 Chemical inventory status

No additional information available

SECTION 16: Other information

Issue date	13/05/2020
Revision date	13/05/2020
Abbreviations and acronyms	ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road ATE - Acute Toxicity Estimate BCF - Bioconcentration factor CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 DMEL - Derived Minimal Effect level

HIT-RE 500 V3, A

Safety Data Sheet

According to SS 586 Part 3: 2014

DNEL - Derived-No Effect Level
IATA - International Air Transport Association
EC50 - Median effective concentration
IMDG - International Maritime Dangerous Goods
LC50 - Median lethal concentration
LD50 - Median lethal dose
LOAEL - Lowest Observed Adverse Effect Level
NOAEC - No-Observed Adverse Effect Concentration
NOAEL - No-Observed Adverse Effect Level
NOEC - No-Observed Effect Concentration
PBT - Persistent Bioaccumulative Toxic
PNEC - Predicted No-Effect Concentration
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS - Safety Data Sheet
vPvB - Very Persistent and Very Bioaccumulative
None.

Other information

Indication of changes			
Section	Changed item	Change	Comments
14	Transportation information	Modified	
16	Additional information	Added	
3	Composition/information on ingredients	Modified	
9	pH	Added	

SDS_SG_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.